Braided Line Rope Socket

The Braided Line Rope Socket is available for use where high pulling forces are anticipated.

The design incorporates a special one-piece Slip and Initiator Clamp arrangement to ensure maximum line pull can be attained with minimal slippage. A Belleville Spring Stack assembly creates a pre-loaded tension to ensure there is very little movement of the termination during upward and downward jarring.

APPLICATIONS

For use with braided line operations to provide connection of the wireline to the toolstring

FEATURES AND BENEFITS

- Incorporates a Peak Heavy-Duty Dual Fish Neck
- One-piece slip assembly for ease of use
- Belleville Spring Stack to minimize cable slippage
- Assembly/disassembly tool provided to aid make up/break out of Slip assembly

TECHNICAL INFORMATION	
Actual OD, in	Fish Neck, in
1.500	1.375 / 1.437
1.750	1.375 / 1.437
1.875	1.750 / 1.812
2.125	1.750 / 1.812
2.500	2.313 / 2.375



All standard industry connections available





Product Code: Braided Line Rope Socket / 123

info@peakwellsystems.com | peakwellsystems.com

© 2017 Peak Well Systems Pty Ltd. All rights reserved.

This material and everything contained herein is the property of Peak Well Systems Pty Ltd and is prepared for information purposes only. Nothing contained within these materials shall be treated as a representation to be relied on by any person or an offer for sale or contract of any kind whatsoever. Any reproduction or distribution without the express written consent of Peak Well Systems Pty Ltd is strictly prohibited. The product to which this datasheet pertains is proprietary technology owned by Peak Well Systems Pty Ltd and patented under numbers referenced herein.