

Tapered Wire Retriever

The Tapered Wire Retriever is used for the process of locating and recovering parted wireline in a single run.

Peak's Tapered Wire Retriever incorporates a unique design feature which allows the Slotted Finder Finger Sleeve to be adjusted to any chosen diameter to suit a range of nominal tubing ID and nipple dimensions.

APPLICATIONS

- Safely locating the top of parted wire
- Latching and retrieving wire back to surface

FEATURES AND BENEFITS

- Peak Adjustable Finder Finger Sleeve
- Extension Bar options
- Multiple Running Neck options
- Robust design
- Inventory reduction

TECHNICAL INFORMATION

Nominal Tubing Size, in	Actual OD, in	Finger Adjustment Range, in
2 3/8	1.750	1.750 - 1.992
2 7/8	2.195	2.195 - 2.441
3 1/2	2.701	2.701 - 2.992
4	3.100	3.100 - 3.548
4 1/2	3.600	3.600 - 3.992
5 1/2	4.530	4.530 - 4.892
7	5.512	5.512 - 6.138

Note: Larger sizes available on request.



Product Code: Tapered Wire Retriever / 213

info@peakwellsystems.com | peakwellsystems.com

© 2017 Peak Well Systems Pty Ltd. All rights reserved.

peak 
WELL SYSTEMS