Crossover

The Peak Crossover is designed to connect two toolstring items with different connections.

Manufactured from the highest quality material, Peak can supply a complete range of Crossovers to suit most readily available connection types.

APPLICATIONS

■ To provide a connection between two toolstring items with different connections

FEATURES AND BENEFITS

- Supplied with industry standard crossover configurations
- Crossovers supplied in both standard and special lengths and diameters to suit operational requirements
- Crossovers can be supplied with third-party proprietary connections to suit customer requirements

TECHNICAL INFORMATION					
Actual OD, in	Pin Connection	Box Connection	Fish Neck, in		
1.875	15/16-in SR	1 1/16-in SR	1.375		
1.875	1 1/16-in SR	15/16-in SR	1.750		
2.125	15/16-in SR	1 1/16-in SR	1.375		
2.125	1 1/16-in SR	15/16-in SR	1.750		
2.500	15/16-in SR	1 9/16-in SR	1.375		
2.500	1 1/16-in SR	1 9/16-in SR	1.750		
2.500	1 9/16-in SR	15/16-in SR	2.313		
2.500	1 9/16-in SR	1 1/16-in SR	2.313		


Actual OD, in	Pin Connection	Pin Connection	Fish Neck, in
1.500	15/16-in SR	15/16-in SR	1.375
1.875	1 1/16-in SR	1 1/16-in SR	1.750
2.125	1 1/16-in SR	1 1/16-in SR	1.750
2.500	1 9/16-in SR	1 9/16-in SR	2.313

Actual OD, in	Box Connection	Box Connection	Fish Neck, in
1.500	15/16-in SR	15/16-in SR	1.375
1.875	1 1/16-in SR	1 1/16-in SR	1.750
2.125	1/16-in SR	1 1/16-in SR	1.750
2.500	1 9/16-in SR	1 9/16-in SR	2.313





Peak Combination Wire Scratcher shown with Sucker Rod Crossover



info@peakwellsystems.com | peakwellsystems.com

© 2017 Peak Well Systems Pty Ltd. All rights reserved.

