



Location: Onshore Malaysia
Customer: Testing Facility
Well Type: 3 ½ and 2 7/8-in horizontal completion tubing (test well)

Products/Services:
SIM Retrievable Bridge Plug
and SIM Running Tool

Case Study Well Barrier and Isolation

SIM Plug Set and Retrieved in Horizontal Wells Using Tractor and Stroker

The Challenge

To evaluate an e-line deployed well tractor, well stroker, and slickline configuration toolstring for mechanical well interventions in highly deviated or horizontal wells.

In high-deviation wells, mechanical well intervention by slickline is often challenging.

A Surface Integration Test (SIT) was conducted to determine the feasibility of mechanical intervention work in 2 7/8-in and 3 ½-in tubing using a well tractor and stroker run on e-line.

A SIM Retrievable Bridge Plug (SIM Plug) using a third-party tractor and stroker tool was run through a horizontal completion

that included a Gas Lift Mandrel, Sliding Sleeve and X Nipple.

The objective of the test was to simulate downhole horizontal conditions and to confirm the plugs could be successfully run, set, and retrieved on e-line using the tractor and stroker.

Considerations

The following key requirements and concerns were highlighted:

- Plug must provide reliable and permanent isolation of the required zone
- Solution to be reliably set and retrieved
- Solution must be quick and easy to deploy on e-line

Peak's Solution

The 3 ½-in SIM Plug was successfully run horizontally through the Gas Lift Mandrel, Sliding Sleeve and X Nipple to the correct setting depth using the tractor.

The stoker tool was activated upwards then downwards to activate the J slot mechanism on the SIM Running Tool. This enabled the slips to engage within the 3 ½-in tubing. Downwards force was then applied by the stoker to successfully set the SIM Plug.

The stoker was used to take a check pull to confirm the SIM Plug was correctly set, and then applied enough force to release the SIM Running Tool, allowing successful retrieval to surface.

To retrieve the SIM Plug, a MAT sub, GS Pulling Tool and pulling probe were run in hole on the tractor and stoker until the GS located the top of the SIM Plug.

The stoker was activated to unset the SIM Plug; the tractor then pulled the SIM Plug out of the completion through the Gas Lift Mandrel, Sliding Sleeve and X Nipple successfully to surface.

The test was repeated with a 2 7/8-in SIM Plug in a 2 7/8-in horizontal completion with success.

Value to Customer

The test proves that Peak's SIM Plug can be run on e-line and mechanically set in horizontal completions using a third-party tractor and stoker to provide the mechanical force required to set the SIM Plug in the tubing.

The test also confirmed that the third-party tractor and stoker could provide the required mechanical force to unset and retrieve the SIM Plug.



▲ GS Pulling Tool

Product Code(s): SIM Retrievable Bridge Plug – 351

info@peakwellsystems.com

© 2019 Peak Well Systems Pty Ltd. All rights reserved. This material and everything contained herein is the property of Peak Well Systems Pty Ltd and is prepared for information purposes only. Nothing contained within these materials shall be treated as a representation to be relied on by any person or an offer for sale or contract of any kind whatsoever. Any reproduction or distribution without the express written consent of Peak Well Systems Pty Ltd is strictly prohibited.

September 2019 | CS-14



▲ SIM Retrievable Bridge Plug

peak 
WELL SYSTEMS